



| order          | description   |
|----------------|---|
| <b>F5P</b>     | switch, 25 amp                                      |
| <b>PX5</b>     | brass male coupler                                  |
| <b>PX29G</b>   | gasket  |
| <b>SR37</b>    | strain relief, metal                                |
| <b>SW101</b>   | main housing  |
| <b>SW102</b>   | stainless steel under carriage                      |
| <b>SW107</b>   | solenoid bracket                                    |
| <b>SW109</b>   | stainless steel vacuum pick-up tool                 |
| <b>SW116</b>   | clamp, motor  |
| <b>SW117</b>   | bearing plate lh                                    |
| <b>SW118</b>   | bearing plate rh                                    |
| <b>SW119</b>   | manifold, spray tip                                 |
| <b>SW122</b>   | pigtail, electrical                                 |
| <b>SW123</b>   | cogged timing belt, for brush                       |
| <b>SW124</b>   | small pulley  |
| <b>SW126</b>   | shaft, brush  |
| <b>SW125</b>   | large pulley  |
| <b>SW128</b>   | bearing housing                                     |
| <b>SW129</b>   | bronze bearing (2 required)                         |
| <b>SW130</b>   | permanent magnet motor                              |
| <b>SW132</b>   | solenoid, mopd, 250 psi (peb)                       |
| <b>SW132-4</b> | solenoid, mopd, 400 psi (peb-tm)                    |
| <b>SW132W</b>  | solenoid, o-ring                                    |
| <b>SW133A</b>  | brass spray nozzle                                  |
| <b>SW134</b>   | spray nozzle .015 1/8" npt stainless steel (peb-tm) |
| <b>SW139</b>   | 1/8" street elbow                                   |
| <b>SW142</b>   | nylon cylindrical brush w/ solid pvc core           |
| <b>SW143</b>   | belt guard  |
| <b>SW144</b>   | hose ring assembly                                  |
| <b>SW145</b>   | 2 amp circuit breaker                               |
| <b>SW146</b>   | 1/8" 45° street elbow                               |
| <b>SW147</b>   | 1/4" bushing  |
| <b>SW148</b>   | 1/8" x 3" nipple                                    |
| <b>SW149</b>   | 1/8" x 1/2" nipple                                  |
| <b>SW150</b>   | female receptacle (mates w/ SW151)                  |
| <b>SW151</b>   | male rubber plug w/ build in strain relief          |
| <b>SW154</b>   | gasket solution/housing                             |
| <b>SW1520</b>  | solenoid switch                                     |
| <b>X8001</b>   | top handle housing                                  |
| <b>X8002</b>   | bottom handle housing                               |
| <b>X80003</b>  | switch lever  |
| <b>X8005</b>   | handle tube   |
| <b>X8006</b>   | switch bracket                                      |
| <b>X8007</b>   | handle grip   |
| <b>X8009</b>   | 4" jumper wire                                      |
| <b>X8010</b>   | switch spring                                       |

| order          | description                              |
|----------------|--|
| <b>X8011B</b>  | handle, tube 1-1/2" w/ bushings          |
| <b>X8012</b>   | handle clamp collar                      |
| <b>X8012A</b>  | handle clamp assembly                    |
| <b>X8016</b>   | knob                                     |
| <b>X8018</b>   | pivot shaft                              |
| <b>X8020</b>   | washer axle                              |
| <b>X8022C</b>  | 2 wire cord assembly                     |
| <b>X8022D</b>  | 3 wire cord assembly                     |
| <b>X8025</b>   | 4" wheel                                 |
| <b>X8026</b>   | dowell pin                               |
| <b>X8027L</b>  | left brace                               |
| <b>X8027R</b>  | right brace                              |
| <b>X8028</b>   | square, washer                           |
| <b>X8029</b>   | axle                                     |
| <b>X8034</b>   | 35 amp rectifier                         |
| <b>X8061</b>   | clip switch lever                        |
| <b>X8100</b>   | counter nut                              |
| <b>X8101</b>   | spring, asher                            |
| <b>X8201</b>   | 8/32" x 3/8" type b screw                |
| <b>X8202</b>   | screw for SW117                          |
| <b>X8206</b>   | 10/32 screw for SW117                    |
| <b>X8208</b>   | 10-24 x 5/8" phillips head machine screw |
| <b>X8210</b>   | wheel screw                              |
| <b>X8210-1</b> | short, switch housing screw and nut      |
| <b>X8220</b>   | long, switch housin screw                |
| <b>X8225</b>   | 3/16" cut washer                         |
| <b>X8228</b>   | spacer                                   |
| <b>X8242</b>   | hex nut                                  |
| <b>X8246</b>   | 5/16 2-1/2" slotted screw                |
| <b>X8247</b>   | phillips flat m/s                        |
| <b>X8247B</b>  | 10/24 x 3/8 phillips pan head screw      |
| <b>X8251</b>   | phillips pan head m/s                    |
| <b>X8254</b>   | shack proof lock washer                  |

### NOT ILLUSTRATED

|                |  |
|----------------|--|
| <b>K1115</b>   | expander, 1-1/2 x 1-1/4                                  |
| <b>K1113G</b>  | 2" cuff  |
| <b>X8150</b>   | solution hose ties                                       |
| <b>1503WD</b>  | tmhd 1-1/2" x 25' blue hose w/ cuffs                     |
| <b>1504WDS</b> | tmhd 1-1/2" x 25' blue hose w/ solution hose & couplings |
| <b>1504WDE</b> | tmhd solution hose & cord assembly                       |
| <b>PX3A</b>    | 25' solution hose w/ couplings 100 psi @ 140° 3/8"       |
| <b>PX28</b>    | insulator boot for toggle switch                         |
| <b>SW141</b>   | 14/3 24' sjtw-a yellow cord                              |
| <b>PCT</b>     | 1" x 260" teflon tape                                    |