

HEPA Certified Wet/Dry Vacuums

Powr-Flite's HEPA wet/dry vacuums are certified with total HEPA filtration at 99.97% rating of efficiency. Both models feature triple filtration for maximum cleaning power while providing excellent dirt retention. The PF25HM and PF35HM are easy to maneuver with 360° swivel casters, while the oversized wheels provide easier movement up and down stairs. The steel wheel/caster support prevents damage to the tank during operation. The swivel hose connector allows the hose to rotate 360°, allowing the operator to safely pull the vacuum by the hose without fear of disconnect or hose entanglement. Both models are UL and CSA listed.

- HEPA certified to 99.97% at 0.3 microns
- Triple filtration
- 20 gauge heavy-duty stainless steel tanks
- Locking style machine to hose coupling
- Comes complete with a tool caddy
- Includes rug, floor, crevice and upholstery tool

H.E.P.A.

For DRY Pick-Up Absolute Filter is precision tested with thermally generated D.O.P. (Di-Octyl Phthalate) Aerosol certified test results on the filter label.



PF25HM 20 gallon Shown

Shipped complete with a heavy duty tool kit!
1-1/2" two-piece curved chrome steel wand,
1-1/2 x 10' crush proof hose, and 4 floor tools –
floor tool, rug tool, crevice and upholstery.

Powr-Flite®

800.880.2913

www.Powr-Flite.com

The Powr-Flite HEPA models are equipped with a HEPA filter system consisting of a certified absolute filter, double layer intermediary glass filter and totally enclosed two ply disposable paper filter system. The HEPA filter is rated with a minimum efficiency of 99.97% at 0.3 microns. Tested using the HOT DOP method @ 94 CFM.

The HEPA filter has a steel outer casing and micro-fibered glass paper filter media separated by corrugated aluminum sheeting that is encased in a protective steel screening. Units are shipped with a 2-pak of intermediary glass filter and a 5-pak of totally enclosed 2-ply bags.

Both models feature double sealed motor bearings with extra shielding to keep moisture and dirt out of the bearings...the main cause of motor failure! Lower motor bearings are contained in steel instead of aluminum housings, so housing will expand at the same rate as the bearing under heat load. This feature prevents replacement of complete housing and dramatically increases bearing life in motor.

The PF25HM and PF35HM also feature a blower hole for blowing debris in hard to reach areas into the vacuum's path and an external power plug for accessories such as the Powr-Flite Powr-Nozzle.

Optional wet conversion kit allows quick conversion for water or hazardous material wet pick-up recovery.



Model PF25HM/PF35HM SPECIFICATIONS

Tank	PF25HM	20 gallon/heavy 20 gauge steel Hospital grade stainless steel
	PF35HM	10 gallon/heavy 20 gauge steel Hospital grade stainless steel
Filter		Certified absolute H.E.P.A. filter, 2-pak intermediary glass filter, filter & 5-pak totally enclosed 2-ply bags
Filtration		Triple
Retention		99.99% of microorganisms
Maximum		to 0.12 micron size particles
Motor		2.5 peak H.P. with high volume blower port
cfm		94
Water Lift		84 inches
Recovery		15 gallons/6 gallons
Power Cord		30 foot, 18/3
Handle		Heavy duty, push handle with 2 position guide
External Plug		For power nozzle
Tool Caddy		Reinforced, vinyl
External Drain		For easy emptying/Not applicable for 10 gallon
Dolly		Reinforced, all-steel
Wheels		Oversized 8" non-scaff
Power Head Clamps		Self-adjusting, heavy duty
Hose		1-1/2" x 10' RCP hose with lock tight swivel connectors
Tools		Rug, floor, crevice, upholstery
Wet Pick-Up Kit		Optional- see price under accessories above
Warranty		1 yr. motor, parts, workmanship
Shipping Weight		83 lbs./59 lbs.



All vacuums are shipped complete with powr-flite's deluxe, heavy duty metal floor tool kits!

Wands are two-piece, 1-1/2" curved chrome steel. Tools consist of a floor tool, rug tool, crevice and upholstery. 10 foot RCP crushproof hose & metal hose couplings with lock-tight swivel connectors.