

Three Models that fit all your job requirements The Professional Choice for Floor Care









Easy pad change and inspection with tilt up position.



Easy pad pressure adjustment with 4 position wheels.



Safety fill tank for preventing overfilling and easy to read fuel level gauge.



Adjustable handle for improved maneuverability.



Easy to change oil filter with drain hose.



Propane Burnisher Specifications			
Model	PB2113	PB2117	PB2717
Pad Size	21" / 53.3 cm	21" / 53.3 cm	27" / 69 cm
Pad Speed	2100 RPM	2100 RPM	1850 RPM
Work Rating	25,000 sq. ft.	25,000 sq. ft.	33,000 sq. ft.
Engine	Kawasaki 431 cc	Kawasaki 494 cc	Kawasaki 494 cc
Horsepower	13 hp	17 hp	17 hp
Engine Speed	3600 RPM	3600 RPM	3600 RPM
Fuel System	regulator system	regulator system	regulator system
Oil Safety System	low oil shut down	low oil shut down	low oil shut down
Starter	110 volt	110 volt	110 volt
Propane Tank	steel safety fill	steel safety fill	steel safety fill
Width	22.75"	22.75"	29.75"
Length	51.5"	51.5"	58.25"
Height	40"	40"	40"
Shipping Weight	220 lbs.	220 lbs.	250 lbs.
Motor warranty*	2 years	2 years	2 years

 * Powr-Flite warranty excludes propane engines and 30 day return policy. See owners manual for manufacture engine warranties.